HIWIN®
上銀科技股份有限公司
台灣408208台中市精密機械園區精科路7號
Tel : +886-4-23594510 Fax : +886-4-23594420
HIWIN TECHNOLOGIES CORP.
No. 7, Jingke Road, Precision Machinery Park, Taichung 408208, Taiwan
www.hiwin.tw business@hiwin.tw

DATORKER® Strain Wave Gear Technical Data

Date: 2026/1/5

Specification	DTH-25-80-AH	Diagram	
Model	25		
Ratio	80		

Item	Value	Unit
Rated torque at input 2000rpm	44	Nm
Average torque	60	Nm
Repeated peak torque	96	Nm
Momentary peak torque	179	Nm
Average input speed	3500	rpm
Maximum input speed	5600	rpm
Moment of inertia	0.793	$x10^{-4}$ kgm^2
Transmission accuracy	1	arc min
Repeatability	±6	arc sec
Maximum backlash	-	arc sec
Hysteresis loss	1	arc min
Lost motion	1	arc min
Torsional Stiffness K1	0.8	kgfm/arc min
Torsional Stiffness K2	1.1	kgfm/arc min
No load starting torque	66	cNm
No load running torque(25℃/2000rpm)	50.8	cNm
Weight	1.4	kg
Crossed roller bearing specifications		
Pitch circle diameter of roller	0.086	m
Offset amount	0.0121	m
Basic dynamic load ratings	10.9	kN
Basic static load ratings	17.9	kN
Moment rigidity	9.2	kgfm/arc min
Permissible dynamic tilting moment	129	Nm
Permissible static tilting moment	210	Nm
Permissible axial load	2.329	kN
Permissible radial load	1.56	kN